Thank you for participating in the Town of Needham self-evaluation survey of the ADA accessibility of our conservation and recreation facilities. Completion of the surveys will allow our community to recognize any shortcomings of the existing programs and develop a plan to remedy them.

| SITE | NAME: | |
|--------|---|--------|
| DATI | E OF SURVEY: | |
| SUR | VEYOR NAME(S): | |
| To cor | nduct the survey, you will need: | |
| • | ADA facility inventory forms | |
| • | A clipboard | |
| • | Pens or pencils | |
| • | A camera | |
| • | A measuring tape | |
| • | A buddy | |
| Before | e you begin the survey, please answer a few quick questions: | |
| 1. | Are you a first time visitor to the conservation property or recreational facility that y surveying? Please circle your response. | ou are |
| | a. Yes | |
| | b. No | |
| 2. | If you answered "yes" to question 1, what are your expectations about the conservation property or recreational facility? What are your first impressions of the conservation property or recreational facility? | |
| | | |
| | | |
| 3. | If you answered "no" to question 1, what is your overall opinion about the state or quality | of the |

| ACTIVITY | EQUIPMENT | ADA REQUIREMENT | YES | NO | NOTES |
|-------------------|-----------------|---|-----|----|-------|
| | | Located adjacent to accessible paths | | | |
| | | Access to Open Spaces | | | |
| | Tables | Back and Arm Rests | | | |
| | | Adequate number | | | |
| | | Located adjacent to accessible paths | | | |
| | Benches | Access to Open Spaces | | | |
| Picnic Facilities | | Back and Arm Rests | | | |
| | | Adequate number | | | |
| | Grills | Height of cooking surface | | | |
| | | Located adjacent to accessible paths | | | |
| | Trash cans | h cans Located adjacent to accessible paths | | | |
| | 5 | Located adjacent to accessible paths | | | |
| | Picnic shelters | Located near accessible water fountains, trash can, restroom, parking, etc. | | | |

| ACTIVITY | EQUIPMENT | ADA REQUIREMENT | YES | NO | NOTES |
|---------------------------|--|---|-----|----|-------|
| | | Surface material | | | |
| | | Dimensions | | | |
| Trails | Not applicable | Rails | | | |
| | | Signage (for visually impaired) | | | |
| | | Trailhead signage (length of trail, typical and minimum width, typical and maximum slope) | | | |
| | | Location from accessible path into water | | | |
| Cuimming Engilities | Danahaa | Handrails | | | |
| Swimming Facilities | ities Beaches | Location from accessible parking | | | |
| | | Shade provided | | | |
| | All play equipment i.e. swings, slides | Same experience provided to all | | | |
| Play Areas (tot lots) | • | Located adjacent to accessible paths | | | |
| | Access routes | Enough space between equipment for wheelchair (3 feet) | | | |
| | Access routes | Located adjacent to accessible paths | | | |
| Game Areas: | | Berm cuts onto courts | | | |
| *ballfield *basketball | Equipment | Height | | | |
| *tennis | | Dimensions | | | |
| | | Spectator seating is accessible | | | |

| ACTIVITY | EQUIPMENT | ADA REQUIREMENT | YES | NO | NOTES |
|----------------------|---|---|-----|----|-------|
| Boat Docks | | Located adjacent to accessible paths | | | |
| | Access Routes | Handrails | | | |
| | _ | Located adjacent to accessible paths | | | |
| | Access Routes | Handrails | | | |
| Fishing Facilities | | Arm Rests | | | |
| risining racinities | Equipment | Bait Shelves | | | |
| | | Handrails | | | |
| | | Fish Cleaning Tables | | | |
| | Are special programs at your facilities accessible? | Learn-to-Swim | | | |
| Programming | | Guided Hikes | | | |
| | accessible: | Interpretive Programs | | | |
| Services and | Information ava impaired | ilable in alternative formats i.e. for visually | | | |
| Technical Assistance | Process to reque interpreter) for | est interpretive services (i.e. sign language meetings | | | |

| Location: | |
|-----------|--|
| | |

| PARKING | | | | |
|--|--|-----|----|---------------------------|
| Total Spaces | Required Accessible Spaces | Yes | No | Comments/Transition Notes |
| Up to 25 | 1 accessible space required | | | |
| 26-50 | 2 spaces | | | |
| 51-75 | 3 spaces | | | |
| 76-100 | 4 spaces | | | |
| 101-150 | 5 spaces | | | |
| 151-200 | 6 spaces | | | |
| 201-300 | 7 spaces | | | |
| 301-400 | 8 spaces | | | |
| 401-500 | 9 spaces | | | |
| Specification for | or Accessible Spaces | Yes | No | Comments/Transition Notes |
| Accessible space | ce located closest to accessible | | | |
| | cannot be located within 200 ft of ance, drop-off area is provided | | | |
| Minimum width of accessible space is 13 ft | | | | |
| Width of accessible space includes 8 ft of space plus 5 ft access aisle | | | | |
| Minimum of 1 van space, 8 ft wide with 8 ft access aisle, for every accessible space provided | | | | |
| If van space is not provided, all accessible spaces are 11 ft wide with 5 ft aisle | | | | |
| Sign with international symbol of accessibility at each space or pair of spaces | | | | |
| Sign minimum 5 ft, maximum 8 ft to top of sign | | | | |
| Surface evenly paved or hard-packed (no cracks) | | | | |
| Surface slope less than 1:20 (5%) | | | | |
| Curbcut to pathway from parking lot at each space or pair of spaces, if sidewalk (curb) is present | | | | |
| sides, has slop | inimum 3 ft wide, excluding sloped ed sides, all slopes not to exceed d textured or painted yellow | | | |

| RAMPS | | | | | | | |
|--|-----|----|---------------------------|--|--|--|--|
| Specification | Yes | No | Comments/Transition Notes | | | | |
| Slope maximum 1:12 (8%) | | | | | | | |
| Minimum width 4 ft between handrails | | | | | | | |
| Handrails on both sides if ramp is longer than 6 ft | | | | | | | |
| Handrails at 34" and 19" from ramp surface | | | | | | | |
| Handrails extend 12" beyond top and bottom | | | | | | | |
| Handgrip oval or round | | | | | | | |
| Handgrip smooth surface | | | | | | | |
| Handgrip diameter between 1¼" and 2" | | | | | | | |
| Clearance of 11/2" between wall and wall rail | | | | | | | |
| Non-slip surface | | | | | | | |
| Level platforms (4 ft x 4 ft) every 30 ft | | | | | | | |
| Level platforms (4 ft x 4 ft) at top and bottom | | | | | | | |
| Level platforms (4 ft x 4 ft) at change of direction | | | | | | | |

| Location: | | _ | |
|--|-----|----|---------------------------|
| SITE ACCESS | | | |
| Specification | Yes | No | Comments/Transition Notes |
| Accessible path of travel from passenger disembarking area and parking area to accessible entrance | | | |
| Disembarking area at accessible entrance | | | |
| Surface evenly paved or hard-packed | | | |
| No ponding of water | | | |

| | | _ | |
|--|-----|----|---------------------------|
| PATH OF TRAVEL, TRAILS | | | |
| Specification | Yes | No | Comments/Transition Notes |
| Path does not require the use of stairs | | | |
| Path is stable, firm, and slip resistant | | | |
| Minimum width of 3 ft | | | |
| Slope maximum 1:20 (5%) and maximum cross pitch is 1:50 (2%) | | | |
| Continuous common surface, no changes in level greater than $\frac{1}{2}$ inch | | | |
| Any objects protruding onto the pathway able to be detected by a person with a visual disability using a cane | | | |
| Objects protruding more than 4" from wall are either within 27" of the ground, or higher than 80" from the ground | | | |
| Trailhead sign identifies length of path, average and minimum width, average and minimum slope | | | |
| Tread obstacles (roots, rocks, gaps between boards) are less than ½" high on concrete, boards, or asphalt, or less than 2" high on any other surface | | | |
| Curbs on the pathway have curbcuts at drives, parking, and drop-offs | | | |

Notes:

Location:

| Location: | |
|-----------|--|
| | |

| PICNICKING, DRINKING FOUNTAINS | | | |
|--|-----|----|---------------------------|
| Specification | Yes | No | Comments/Transition Notes |
| Picnicking | | | |
| At least 5% of the total tables are accessible with clear space under the table top being at least 30" wide and 48" deep per seating space and not less than 27" clear from the ground to the underside of the table | | | |
| For tables without toe clearance, the knee space under the table is at least 28" high, 30" wide, and 24" deep | | | |
| Top of table no higher than 32" above ground | | | |
| Surface of the clear ground space under and around the table is stable, firm and slip-resistant, and evenly graded with a maximum slope of 2% in all directions | | | |
| Accessible tables, grills and fire rings have clear ground space of at least 36" around the perimeter | | | |
| Drinking Fountains | | | |
| Spouts no higher than 36" from floor to outlet | | | |
| Hand operated push button or level controls | | | |
| Spouts located near front with stream of water as parallel to front as possible | | | |
| If recessed, recess a minimum 30" width, and no deeper than depth of fountain | | | |
| If no clear knee space underneath, clear floor space 30" x 48" to allow parallel approach | | | |

| Location: | | |
|-----------|--|--|
| | | |

| ENTRANCES, FLOORS | | | | | |
|---|-----|----|---------------------------|--|--|
| Specification | Yes | No | Comments/Transition Notes | | |
| Entrances | | | | | |
| Primary public entrances accessible to person using wheelchair, must be signed, gotten to independently, and <i>not</i> be the service entrance | | | | | |
| Level space extending 5 ft. from the door, interior and exterior of entrance doors | | | | | |
| Minimum 32" clear width opening (i.e. 36" door with standard hinge) | | | | | |
| At least 18" clear floor area on latch, pull side of door | | | | | |
| Door handle no higher than 48" and operable with a closed fist | | | | | |
| Vestibule is 4 ft plus the width of the door swinging into the space | | | | | |
| Entrance(s) on a level that makes elevators accessible | | | | | |
| Door mats less than $\frac{1}{2}$ " thick are securely fastened | | | | | |
| Door mats more than ½" thick are recessed | | | | | |
| Grates in path of travel have openings of ½" maximum | | | | | |
| Signs at non-accessible entrance(s) indicate direction to accessible entrance | | | | | |
| Emergency egress – alarms with flashing lights and audible signals, sufficiently lighted | | | | | |
| Floors | | | | | |
| Non-slip surface | | | | | |
| Carpeting is high-density, low pile, non- absorbent, stretched taut, securely anchored | | | | | |
| Corridor width minimum is 3 ft | | | | | |
| Objects (signs, ceiling lights, fixtures) only protrude 4" into the path of travel from a height of 27" to 80" above the floor | | | | | |

| STAIRS and DOORS | | | | | |
|---|-----|----|---------------------------|--|--|
| Specification | Yes | No | Comments/Transition Notes | | |
| Stairs | | | | | |
| No open risers | | | | | |
| Nosings (stair edges) not projecting | | | | | |
| Treads at least 11" wide | | | | | |
| Handrails on both sides | | | | | |
| Handrails 34"-38" above tread | | | | | |
| Handrail extends a minimum of 1 ft beyond top and bottom riser (if not a safety hazard and space permits) | | | | | |
| Handgrip oval or round | | | | | |
| Handgrip has a smooth surface | | | | | |
| Handgrip diameter between 1¼" and 1½" | | | | | |
| 1½" clearance between wall and handrail | | | | | |
| Doors | | | | | |
| Minimum 32" clear opening | | | | | |
| At least 18" clear floor space on pull side of door | | | | | |
| Closing speed minimum 3 seconds to within 3" of the latch | | | | | |
| Interior doors have a maximum 5 lbs pressure | | | | | |
| Threshold maximum ½" high, beveled on both sides | | | | | |
| Hardware operable with a closed fist (no conventional door knobs or thumb latch devices) | | | | | |
| Hardware minimum 36", maximum 48" above the floor | | | | | |
| Clear, level floor space extends out 5 ft from both sides of the door | | | | | |
| Door adjacent to revolving door is accessible and unlocked | | | | | |
| Doors opening into hazardous area have hardware that has a roughened surface | | | | | |

| RESTROOMS – also see Doors and Vestibules | | | |
|---|-----|-----|---------------------------|
| Specification | Yes | No | Comments/Transition Notes |
| 5 ft turning space measured 12" from the floor | | | |
| At least one sink: | | | |
| Clear floor space of 30" by 48" to allow a forward approach | | | |
| Mounted without pedestal or legs, height 34" to top of rim | | | |
| Extends at least 22" from the wall | | | |
| Open knee space a minimum 19" deep, 30" width, and 27" high | | | |
| Cover exposed pipes with insulation | | | |
| Faucets operable with closed fist (lever or spring activated handle) | | | |
| At least one stall: | • | | |
| Accessible to person using wheelchair at 60" wide by 72" deep | | | |
| Stall door is 36" wide | | | |
| Stall door swings out | | | |
| Stall door is self-closing | | | |
| Stall door has a pull latch | | | |
| Lock on stall door is operable with a closed fist, and 32" above the floor | | | |
| Coat hook is 54" high | | | |
| Toilet | ı | II. | |
| 18" from center to nearest side wall | | | |
| 42" minimum clear space from center to farthest wall or fixture | | | |
| Top of seat 17"-19" above the floor | | | |
| Grab Bars | l | 1 | |
| On back and side wall closest to toilet | | | |
| 1¼" diameter | | | |
| 1½" clearance to wall | | | |
| Located 30" above and parallel to the floor | | | |
| Acid-etched or roughened surface | | | |
| 42" long | | | |
| Fixtures | | | |
| Toilet paper dispenser is 24" above floor | | | |
| One mirror set a maximum 38" to bottom (if tilted, 42") | | | |
| Dispensers (towel, soap, etc.) at least one of each a maximum 42" above the floor | | | |
| Notes: | • | _ | |

| Location: | | _ | | |
|--|-----|----|---------------------------|--|
| Switches, Controls, & Signs | | | | |
| Specification | Yes | No | Comments/Transition Notes | |
| Switches and Controls | | | | |
| Switches and controls for light, heat, windows, ventilation, fire alarms, thermostats, thermostats, etc., are a minimum of 36" and a maximum of 48" above the floor for a forward reach, and a maximum of 54" for a side reach | | | | |
| Electrical outlets centered no lower than 18" above the floor | | | | |
| Warning signals are visual as well as audible | | | | |
| Signs | | • | | |
| Mounting height is 60" to centerline of the sign | | | | |
| Within 18" of door jamb or recessed | | | | |
| Letters and numbers at least 1¼" high | | | | |
| Letters and numbers raised .03" | | | | |
| Letters and numbers contrast with the background color | | | | |